



P.O. BOX 16344 • 520 BROOME ROAD • GREENSBORO, NC 27406
TELEPHONE 336-378-0965 • FAX 336-272-4312
www.unitexchemical.com

Uniplex 546

TRI (2-ETHYL HEXYL) TRIMELLITATE (TOTM)

Uniplex 546 is an excellent low volatility plasticizer for polyvinyl chloride. It is particularly recommended for use in PVC wire insulation.

SPECIFICATIONS:

Appearance	Clear liquid, free of foreign material
Odor	Mild, characteristic
Assay	99.0% minimum
Acidity, as Trimellitic Acid, wt %	0.02 maximum
Color, APHA	100 maximum, Typical 70 or less
Water Content, wt %	0.1 maximum
Specific Gravity, 20/20°C	0.989 – 0.995

HANDLING INFORMATION:

Refer to Material Safety Data Sheet

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any patents.

Uniplex 546		Date Issued: 11/17/09
www.unitexchemical.com	Page 1 of 1	Supersedes: 11/4/92